



B503-09A1 Lemon Yellow Solar Lux Stain

# MATERIAL SAFETY DATA SHEET

RPM Wood Finishes Group  
3194 Hickory Boulevard  
Hudson, North Carolina 28638  
828-728-8266

EMERGENCY PHONE (CHEM TREC): ..... 1-800-424-9300  
FOR ALL INTERNATIONAL TRANSPORTATION ACCIDENTS. .... 1-703-527-3887 (collect)

Health: 2                      Flammability: 3                      Reactivity 0

PRODUCT NAME: B503-09A1 Lemon Yellow Solar Lux Stain

## I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

REVISION DATE: 25/09/03  
SUPERCEDES: 16/09/03  
MSDS NO. B503-09A1

## II. COMPOSITION/INFORMATION ON INGREDIENTS

| CHEMICAL NAME                     | %     | CAS #      | PEL                        |
|-----------------------------------|-------|------------|----------------------------|
| Methanol                          | 71-80 | 67-56-1    | 200 ppm TWA; 260 mg/m3 TWA |
| Diethylene glycol monoethyl ether | 11-20 | 111-90-0   | No PEL established         |
| Acid Yellow 49                    | 1-10  | 69762-08-9 | No PEL established         |

## III. HAZARDS IDENTIFICATION

**Routes of Entry:** Inhalation., Absorption., Ingestion., Skin contact., Eye contact.  
**Medical Conditions Aggravated:** Eye disease. Skin disease including eczema and sensitization. Digestive tract disease. Respiratory disease including asthma and bronchitis.

### Immediate (Acute) Health Effects

**Inhalation:** Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.

**Skin Contact:** Can cause minor skin irritation, defatting, and dermatitis.

**Eye Contact:** Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.

**Skin Absorption:** Contains methanol. Upon prolonged or repeated exposure, may cause deterioration of the optic nerve if large quantities are absorbed through the skin. Repeated absorption of large quantities may lead to blindness. No absorption hazard in normal industrial use.

**Ingestion:** Ingestion of this product may result in central nervous system effects including headache, sleepiness, dizziness, slurred speech and blurred vision. Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea.

**Target Organ Acute Toxicity:**  
Methyl alcohol skin, eyes, CNS, GI tract, respiratory system

**Long-Term (Chronic) Health Effects:**

**Carcinogenicity:** None of the substances have been shown to cause cancer in long term animal studies. Not a carcinogen according to NTP, IARC, or OSHA.

**Mutagenicity:** No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

**Inhalation:** Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.

**Skin Contact:** Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and dermatitis.

**Eye Contact:** Upon prolonged or repeated contact, can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.

**Skin Absorption:** Upon prolonged or repeated exposure, harmful if absorbed through the skin. May cause severe irritation and systemic damage.

**Target Organ Chronic Toxicity:** Eyes. Skin. Digestive Tract. Nervous System. Respiratory Tract.

**Supplemental Health Hazard Information:** No additional health information available.

**IV. FIRST AID**

**Inhalation:** Remove to fresh air. Get medical attention immediately. Have a trained individual administer humidified oxygen. If not breathing, give artificial respiration. Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen.

**Eyes:** Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

**Skin Contact:** Wash with soap and water. Get medical attention if irritation develops or persists.

**Ingestion:** Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this MSDS. Minimal risk of harm if swallowed. Do not induce vomiting. Seek medical attention immediately. Provide medical care provider with this MSDS.

**Notes to MD:** No additional first aid information available.

**V. FIRE FIGHTING MEASURES**

**Flammability Summary:**

**Flash Point:** 54 (CALC.) °F  
**Upper Flammable/Explosive Limit, % in air:** 9.0 @ 77° F  
**Lower Flammable/Explosive Limit, % in air:** 1.2 @ 77° F

**Fire Hazards:** Vapors are heavier than air and can travel to a source of ignition and flash back. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death. Material may be ignited if preheated to temperatures above the flash point in the presence of a source of ignition.

**Fire Fighting Instructions:** Water spray may be used to cool containers however be careful not to spread the fire with the water used for cooling purposes. Use methods for the surrounding fire. Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products.

**Hazardous Combustion Products:** Carbon monoxide

## **VI. ACCIDENTAL RELEASE MEASURES**

**Health Consideration for Spill Response:** Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

**Spill Mitigation Procedures General Methods:** Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

## **VII. HANDLING AND STORAGE**

**Handling:** Wash thoroughly after handling. Keep in air-tight containers- material is hygroscopic. Do not reuse containers. Avoid breathing vapors from heated material. Harmful or irritating material. Avoid contact and avoid breathing the material. Use only in a well ventilated area.

**Storage:** Store this product in air-tight containers. Keep away from heat, sparks, and flame. Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed.

## VIII. ENGINEERING CONTROLS AND PERSONAL PROTECTIVE EQUIPMENT

---

**Engineering Controls:** Facilities storing or using this material should be equipped with an eyewash and safety shower. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. No exposure limits exist for the constituents of this product. Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort.

### Protective Equipment

**Respiratory Tract:** Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2-1992). A written respiratory protection program, including provisions for medical certification, training, fit testing, exposure assessments, maintenance, inspection, cleaning, and convenient, sanitary storage should be implemented.

**Eyes:** Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available.

**Skin:** Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

## IX. PHYSICAL DATA

---

|                              |                           |
|------------------------------|---------------------------|
| <b>Physical State:</b>       | COLORED LIQUID            |
| <b>Odor:</b>                 | MODERATELY STRONG ALCOHOL |
| <b>Solids Vol %:</b>         | 2.032                     |
| <b>Solids Wt %:</b>          | 3.7945                    |
| <b>Material VOC lbs/gal:</b> | 6.5391                    |
| <b>Material VOC gms/l:</b>   | 785.2925                  |
| <b>Coatings VOC lbs/gal:</b> | 6.6934                    |
| <b>Coatings VOC gms/l:</b>   | 803.8221                  |
| <b>Weight per gallon:</b>    | 7.0125                    |

## X. STABILITY AND REACTIVITY

---

**Stability Information:** Stable under normal conditions.

**Conditions to Avoid:** None known.

**Chemical Incompatibility:** Strong oxidizing agents.

## XI. TOXICOLOGICAL INFORMATION

---

| Chemical Name                | CAS Number | LD50/LC50  |
|------------------------------|------------|--|
| Methanol                     | 67-56-1    | Inhalation LC50 Rat : 64000 ppm/4H; Oral LD50 Rat : 5628 mg/kg; Oral LD50 Mouse : 7300 mg/kg; Dermal LD50 Rabbit : 15800 mg/kg |
| Ethanol, 2-(2-ethoxyethoxy)- | 111-90-0   | Oral LD50 Rat : 5500 mg/kg; Oral LD50 Mouse : 6600 mg/kg; Dermal LD50 Rabbit : 4200 uL/kg                                      |

## XII. ECOLOGICAL INFORMATION

**Overview (for ingredients):** No data available. This material is not expected to be harmful to the ecology.

## XIII. DISPOSAL CONSIDERATIONS

**Waste Description for Spent Product:** Spent or discarded material is a hazardous waste. Spent or discarded material is not expected to be a hazardous waste.

**Disposal Methods:** Comply with all Local, State, Federal, and Provincial Environmental Regulations. Dispose of by incineration following Federal, State, Local, or Provincial regulations.

**Potential EPA Waste Codes:** If discarded, this product is considered a RCRA ignitable waste, D001.

### **Components Subject to USEPA Land Disposal Restrictions:**

|          |         |         |
|----------|---------|---------|
| Methanol | 67-56-1 | 77.61 % |
|----------|---------|---------|

## XIV. TRANSPORTATION INFORMATION

**DOT** Paint, 3, UN 1263, II

## XV. REGULATORY INFORMATION

| <b>Chemical Name</b>              | <b>Regulation</b>         | <b>CASRN</b> | <b>%</b> |
|-----------------------------------|---------------------------|--------------|----------|
| Methanol                          | SARA 313 Reportable:      | 67-56-1      | 77.61    |
| Methanol                          | New Jersey Right To Know: | 67-56-1      | 77.61    |
| Diethylene glycol monoethyl ether | New Jersey Right To Know: | 111-90-0     | 15.85    |
| Acid Yellow 49                    | New Jersey Right To Know: | 69762-08-9   | 3.79     |

## XVI. ADDITIONAL INFORMATION

**Other Information:** IMPORTANT: WHILE THE DESCRIPTIONS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU PERFORM AN ASSESSMENT TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED, DATA OR INFORMATION SET FORTH. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, OR DATA PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, THE DESCRIPTIONS, DATA AND INFORMATION FURNISHED HEREUNDER ARE GIVEN GRATIS. NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DATA AND INFORMATION GIVEN ARE ASSUMED. ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

MSDS glossary.