



B611-0631 Quala Lacquer Thinner

# MATERIAL SAFETY DATA SHEET

RPM Wood Finishes Group  
3194 Hickory Boulevard  
Hudson, North Carolina 28638  
828-728-8266

EMERGENCY PHONE (CHEM TREC): ..... 1-800-424-9300  
FOR ALL INTERNATIONAL TRANSPORTATION ACCIDENTS. .... 1-703-527-3887 (collect)

Health: 2                      Flammability: 3                      Reactivity 0

PRODUCT NAME: B611-0631 Quala Lacquer Thinner

## I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

REVISION DATE: 26/02/02  
SUPERCEDES: None  
MSDS NO. B611-0631

## II. COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME	%	CAS #	PEL
isopropanol	31-40	67-63-0	400 ppm TWA; 980 mg/m3 TWA
Hydrotreated distillate, light acetone	31-40	68410-97-9	No PEL established
Ethyl Acetate	11-20	67-64-1	1000 ppm TWA; 2400 mg/m3 TWA
n-Butyl acetate	11-20	141-78-6	400 ppm TWA; 1400 mg/m3 TWA
	11-20	123-86-4	150 ppm TWA; 710 mg/m3 TWA

## III. HAZARDS IDENTIFICATION

**Routes of Entry:** Inhalation, ingestion, skin, eyes.  
**Medical Conditions Aggravated:** Skin disease including eczema and sensitization. Respiratory disease including asthma and bronchitis. Eye disease.

### Immediate (Acute) Health Effects

**Inhalation:** Irritation may be delayed for several hours. Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.

**Skin Contact:** Substance causes moderate skin irritation. Contact with the eyes may cause moderate to severe eye injury. Eye contact may result in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible.

**Eye Contact:** Mildly irritating but will not injure eye tissue. Contact with the eyes may cause moderate to severe eye injury. Eye contact may result in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible.

**Skin Absorption:** Minimal hazard in normal industrial use. May cause gastrointestinal discomfort.

**Ingestion:** Harmful if swallowed. Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea.

**Target Organ Acute Toxicity:**

Isopropyl alcohol	eyes, skin, respiratory system
Acetone	respiratory system, skin, eyes, CNS
Ethylacetate	eyes, skin, respiratory system
n-Butyl acetate	eyes, skin, respiratory system, CNS

**Long-Term (Chronic) Health Effects:**

**Carcinogenicity:** None of the substances have been shown to cause cancer in long term animal studies. Not a carcinogen according to NTP, IARC, or OSHA.

**Reproductive and Developmental Toxicity:** No information available.

**Mutagenicity:** No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

**Skin Contact:** Prolonged or repeated contact may cause irritation.

**Target Organ Chronic Toxicity:** Skin. Respiratory Tract. Eyes. Nervous System. Skin.

**Supplemental Health Hazard Information:** No additional health information available.

**IV. FIRST AID**

---

**Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Remove to fresh air. Get medical attention immediately. Have a trained individual administer humidified oxygen. If not breathing, give artificial respiration.

**Eyes:** Seek medical advice if symptoms persist. Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.

**Skin Contact:** Wash with soap and water. Wash with soap and water. Get medical attention if irritation develops or persists.

**Ingestion:** Never give anything by mouth to an unconscious person. Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this MSDS.

Notes to MD: No additional first aid information available.

## V. FIRE FIGHTING MEASURES

---

### Flammability Summary:

**Flash Point:** -22C; -8F  
**Autoignition Temperature:** 0 deg. C  
**Upper Flammable/Explosive Limit, % in air:** 12.8 @ 77° F  
**Lower Flammable/Explosive Limit, % in air:** 2.0 @ 77° F

**Fire Hazards:** Flammable Liquid. Can release vapors that form explosive mixtures at temperatures at or above the flash point. Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a Class B fire. Vapors are heavier than air and may travel to a source of ignition and flash back.

**Extinguishing Media:** Use alcohol resistant spray, Carbon Dioxide, water spray or dry chemical to extinguish a fire involving this chemical. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. H<sub>2</sub>O, CO<sub>2</sub>, dry chemical, foam. Carbon dioxide Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water spray or fog may also be effective for extinguishing if swept across the base of the fire. Water can also be used to absorb heat and keep exposed material from being damaged by fire.

**Fire Fighting Instructions:** Flammable Liquid. Can release vapors that form explosive mixtures at temperatures at or above the flash point. Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a Class B fire. Vapors are heavier than air and may travel to a source of ignition and flash back.

**Hazardous Combustion Products:** Carbon dioxide, Carbon monoxide

## VI. ACCIDENTAL RELEASE MEASURES

---

**Health Consideration for Spill Response:** No health affects expected from the clean-up of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section VIII of this MSDS

**Spill Mitigation Procedures General Methods:** Gather and store in a sealed container pending a waste disposal evaluation. Avoid runoff into storm sewers and ditches that lead to waterways. No special spill clean-up considerations. Collect and discard in regular trash.

## VII. HANDLING AND STORAGE

---

**Handling:** Use spark-proof tools and explosion-proof equipment.

**Storage:** Keep away from heat, sparks, and flame. Keep away from sources of ignition.

## VIII. ENGINEERING CONTROLS AND PERSONAL PROTECTIVE EQUIPMENT

---

**Engineering Controls:** Ventilation should effectively remove and prevent buildup of any vapor/mist/fume generated from the handling of this product.

## **Protective Equipment**

### **Respiratory Tract:**

Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2-1992). A written respiratory protection program, including provisions for medical certification, training, fit testing, exposure assessments, maintenance, inspection, cleaning, and convenient, sanitary storage should be implemented.

### **Eyes:**

Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available.

### **Skin:**

Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

## **IX. PHYSICAL DATA**

<b>Physical State:</b>	CLEAR LIQUID
<b>Odor:</b>	STRONG SOLVENT
<b>Solids Vol %:</b>	0
<b>Solids Wt %:</b>	0
<b>Material VOC lbs/gal:</b>	5.7192
<b>Material VOC gms/l:</b>	686.823
<b>Weight per gallon:</b>	6.6653

## **X. STABILITY AND REACTIVITY**

<b>Stability Information:</b>	Stable.
<b>Conditions to Avoid:</b>	Avoid: heat, sparks, flame and oxidizing agents.
<b>Chemical Incompatibility:</b>	Strong oxidizing agents. Strong acids. Strong alkalies.

## **XI. TOXICOLOGICAL INFORMATION**

<b>Chemical Name</b>	<b>CAS Number</b>	<b>LD50/LC50</b>
Isopropyl alcohol	67-63-0	Inhalation LC50 Rat : 16000 ppm/8H; Oral LD50 Rat : 5045 mg/kg; Oral LD50 Mouse : 3600 mg/kg; Dermal LD50 Rabbit : 12800 mg/kg
Acetone	67-64-1	Inhalation LC50 Rat : 50100 mg/m <sup>3</sup> /8H; Inhalation LC50 Mouse : 44 gm/m <sup>3</sup> /4H; Oral LD50 Rat : 5800 mg/kg; Oral LD50 Mouse : 3 gm/kg
Acetic acid, ethyl ester	141-78-6	Inhalation LC50 Rat : 200 gm/m <sup>3</sup> ; Inhalation LC50 Mouse : 45 gm/m <sup>3</sup> /2H; Oral LD50 Rat : 5620 mg/kg; Oral LD50 Mouse : 4100 mg/kg; Dermal LD50 Rabbit : >20 mL/kg
Acetic acid, butyl ester	123-86-4	Inhalation LC50 Rat : 2000 ppm/4H; Inhalation LC50 Mouse : 6 gm/m <sup>3</sup> /2H; Oral LD50 Rat : 10768 mg/kg; Oral LD50 Mouse : 6 gm/kg; Dermal LD50 Rabbit : >17600 mg/kg

## **XII. ECOLOGICAL INFORMATION**

**Overview (for ingredients):** Keep out of waterways.

### **Ecological Toxicity Values:**

### **XIII. DISPOSAL CONSIDERATIONS**

---

**Waste Description for Spent Product:** The waste may be a listed and/or characteristic hazardous waste. The waste may be a listed hazardous waste. Spent or discarded material is a hazardous waste.

**Disposal Methods:** Comply with all Local, State, Federal, and Provincial Environmental Regulations. Dispose of by incineration following Federal, State, Local, or Provincial regulations.

**Potential EPA Waste Codes:** If discarded, this product is considered a RCRA ignitable waste, D001.

**Components Subject to USEPA Land Disposal Restrictions:**

Acetone	67-64-1	14.00 %
Ethylacetate	141-78-6	12.00 %

### **XIV. TRANSPORTATION INFORMATION**

---

**DOT** Paint 3 UN1263 PG II  
Quart or less ORM-D\*\*\*Label:None

### **XV. REGULATORY INFORMATION**

---

Toxic Substances Control Act (TSCA): A component (or components) of this product is not listed on the TSCA Inventory of Existing Chemical Substances.

<b>Chemical Name</b>	<b>Regulation</b>	<b>CASRN</b>	<b>%</b>
Isopropyl alcohol	SARA 313 Reportable:	67-63-0	32.00
isopropanol	New Jersey Right To Know:	67-63-0	32.00
Hydrotreated distillate, light acetone	New Jersey Right To Know:	68410-97-9	30.00
acetone	New Jersey Right To Know:	67-64-1	14.00
Ethyl Acetate	New Jersey Right To Know:	141-78-6	12.00
n-Butyl acetate	New Jersey Right To Know:	123-86-4	12.00

### **XVI. ADDITIONAL INFORMATION**

---

**Other Information:** IMPORTANT: WHILE THE DESCRIPTIONS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU PERFORM AN ASSESSMENT TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED, DATA OR INFORMATION SET FORTH. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, OR DATA PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, THE DESCRIPTIONS, DATA AND INFORMATION FURNISHED HEREUNDER ARE GIVEN GRATIS. NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DATA AND INFORMATION GIVEN ARE ASSUMED. ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

MSDS glossary.