



B744-004 Natural W/B Wood Filler Paste

# MATERIAL SAFETY DATA SHEET

RPM Wood Finishes Group  
3194 Hickory Boulevard  
Hudson, North Carolina 28638  
828-728-8266

EMERGENCY PHONE (CHEM TREC): ..... 1-800-424-9300  
FOR ALL INTERNATIONAL TRANSPORTATION ACCIDENTS. .... 1-703-527-3887 (collect)

Health: 1                      Flammability: 0                      Reactivity 0

PRODUCT NAME: B744-004 Natural W/B Wood Filler Paste

## I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

REVISION DATE: 25/09/03  
SUPERCEDES: 22/07/02  
MSDS NO. B744-004

## II. COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME	%	CAS #	PEL
calcium carbonate	31-40	471-34-1	No PEL established
Barium Sulfate	21-30	7727-43-7	total dust: 15 mg/m3 TWA; respirable fraction: 5 mg/m3 TWA
Emulsion			No PEL established
acrylic non volatiles	1-10	PROPRIETARY	No PEL established
propylene glycol	1-10	57-55-6	No PEL established
titanium dioxide	1-10	13463-67-7	total dust: 15 mg/m3 TWA
Quartz	<1	14808-60-7	see Table Z-3
Ammonia	<1	7664-41-7	50 ppm TWA; 35 mg/m3 TWA

## III. HAZARDS IDENTIFICATION

**Routes of Entry:** Inhalation., Ingestion., Skin contact., Eye contact.  
**Medical Conditions Aggravated:** Eye disease. Respiratory disease including asthma and bronchitis. Skin disease including eczema and sensitization.

### Immediate (Acute) Health Effects

**Inhalation:** Causes respiratory tract irritation. Chronic lung disease (silicosis) and/or lung cancer may result from prolonged/repeated breathing of the dust of this material. Can be corrosive to the respiratory tract causing severe irritation and tissue damage.

**Skin Contact:** May cause skin irritation. Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage. Corrosive to skin tissue. Can cause chemical burns.

**Eye Contact:** Can cause mechanical irritation if dusts are generated. Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue. Corrosive to eye tissue. Can cause severe irritation, tearing, and burns that can quickly lead to permanent injury including blindness.

**Skin Absorption:** No component(s) in this product is known to be absorbed through the skin. No absorption hazard in normal industrial use.

**Ingestion:** No hazard in normal industrial use. Irritating to mouth, throat, and stomach. Corrosive to tissue. Can cause severe and permanent damage to mouth, throat, stomach. Aspiration may lead to lung damage.

**Target Organ Acute Toxicity:**

Barium sulfate	respiratory system, eyes
Titanium dioxide	respiratory system (in animals: lung tumors)
Silica, crystalline	respiratory system, eyes (in animals: lung cancer)
Ammonia	respiratory system, eyes, skin

**Long-Term (Chronic) Health Effects:**

**Carcinogenicity:** Not listed by ACGIH, IARC, NIOSH, NTP or OSHA. None of the substances have been shown to cause cancer in long term animal studies. Not a carcinogen according to NTP, IARC, or OSHA.

**Reproductive and Developmental Toxicity:** No information available. Contains a substance(s) that is a possible reproductive system hazard based on high dose tests with laboratory animals.

**Mutagenicity:** No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

**Inhalation:** Upon prolonged and/or repeated exposure, can be corrosive to the respiratory tract causing severe irritation and tissue damage.

**Skin Contact:** Prolonged or repeated contact may cause irritation. Upon prolonged or repeated contact, corrosive to skin tissue. Can cause chemical burns.

**Eye Contact:** Upon prolonged or repeated contact, dust contact can cause mechanical irritation. Upon prolonged or repeated contact, may become corrosive to eye tissue. Can cause severe irritation, tearing, and burns that can lead to permanent injury including blindness.

**Skin Absorption:** Skin sensitization, characterized by redness, inflammation, itching and/or burning may result from prolonged or repeated contact with this material. Upon prolonged or repeated exposure, no hazard in normal industrial use.

**Target Organ Chronic Toxicity:** Nervous System. Eyes. Respiratory Tract. Skin.

**Supplemental Health Hazard Information:** No additional health information available.

**IV. FIRST AID**

---

**Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen.

**Eyes:** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Have eyes examined and tested by medical personnel. Use an eye wash to remove a chemical from your eye regardless of the level of hazard. Flush the affected eye for at least twenty minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical advice after flushing.

**Skin Contact:** Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists. Wash with soap and water. Get medical attention if irritation develops or persists. Wash with soap and water under a drench shower. Remove contaminated clothing, launder immediately, and discard contaminated leather goods. Get medical attention immediately.

**Ingestion:** Minimal risk of harm if swallowed. Do not induce vomiting. Seek medical attention immediately. Provide medical care provider with this MSDS.

**Notes to MD:** No additional first aid information available.

## **V. FIRE FIGHTING MEASURES**

### **Flammability Summary:**

**Flash Point:** >200 (CALC.) °F  
**Upper Flammable/Explosive Limit, % in air:** 12.6 @ 77° F  
**Lower Flammable/Explosive Limit, % in air:** 2.6 @ 77° F

**Fire Hazards:** Use process enclosures to control the level of dust in the air. Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back.

**Extinguishing Media:** Use methods suitable to fight surrounding fire.

**Fire Fighting Instructions:** Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products.

**Hazardous Combustion Products:** Carbon monoxide Ammonia Hydrogen Nitrogen containing gases

## **VI. ACCIDENTAL RELEASE MEASURES**

**Health Consideration for Spill Response:** No health affects expected from the clean-up of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section VIII of this MSDS

**Spill Mitigation Procedures General Methods:** No special spill clean-up considerations. Collect and discard in regular trash.

## **VII. HANDLING AND STORAGE**

**Handling:** Wash thoroughly after handling. Avoid contact with material. Keep in air-tight containers- material is hygroscopic. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Minimize dust generation and accumulation. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Do not enter storage area unless adequately ventilated. Remove contaminated clothing and wash before reuse. Mildly irritating material. Avoid unnecessary exposure.

**Storage:** Keep from freezing. No special requirements.

---

## **VIII. ENGINEERING CONTROLS AND PERSONAL PROTECTIVE EQUIPMENT**

---

**Engineering Controls:** Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Facilities storing or using this material should be equipped with an eyewash and safety shower. No exposure limits exist for the constituents of this product. Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort.

### **Protective Equipment**

**Respiratory Tract:** Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2-1992). A written respiratory protection program, including provisions for medical certification, training, fit testing, exposure assessments, maintenance, inspection, cleaning, and convenient, sanitary storage should be implemented.

**Eyes:** Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available.

**Skin:** Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

---

## **IX. PHYSICAL DATA**

---

<b>Physical State:</b>	COLORED VISCOUS LIQUID
<b>Odor:</b>	MILD AMINE
<b>Solids Vol %:</b>	53.2776
<b>Solids Wt %:</b>	74.6037
<b>Material VOC lbs/gal:</b>	1.0301
<b>Material VOC gms/l:</b>	123.7023
<b>Coatings VOC lbs/gal:</b>	1.5738
<b>Coatings VOC gms/l:</b>	188.9964
<b>Weight per gallon:</b>	15.4253

---

## **X. STABILITY AND REACTIVITY**

---

**Stability Information:** Stable for one year when stored in a cool dry place. Stable. Stable under normal conditions.

**Conditions to Avoid:** Contamination. Visible light. None known.

**Chemical Incompatibility:** Acids. Aluminum alloys. Ammonia. Strong reducing agents. Metals. Strong oxidizing agents. Strong acids.

**Hazardous Polymerization:** Hazardous Polymerization will not occur.

## **XI. TOXICOLOGICAL INFORMATION**

<b>Chemical Name</b>	<b>CAS Number</b>	<b>LD50/LC50</b>
Carbonic acid, calcium salt (1:1)	471-34-1	Oral LD50 Rat : 6450 mg/kg
1,2-Propanediol	57-55-6	Oral LD50 Rat : 20 gm/kg; Oral LD50 Mouse : 22 gm/kg; Dermal LD50 Rabbit : 20800 mg/kg
Ammonia	7664-41-7	Inhalation LC50 Rat : 2000 ppm/4H; Inhalation LC50 Mouse : 4230 ppm/1H

## **XII. ECOLOGICAL INFORMATION**

**Overview (for ingredients):** No data available. This material is not expected to be harmful to the ecology.

## **XIII. DISPOSAL CONSIDERATIONS**

**Waste Description for Spent Product:** Mixing spent or discarded material with other materials may render the mixture hazardous. Perform a hazardous waste determination on mixtures. The waste is a listed hazardous waste. Spent or discarded material is not expected to be a hazardous waste.

**Disposal Methods:** Comply with all Local, State, Federal, and Provincial Environmental Regulations. Perform waste water treatment. Dispose of in a landfill. Disposal is not likely to be regulated.

### **Components Subject to USEPA Land Disposal Restrictions:**

No chemicals subject to land disposal restrictions. %

## **XIV. TRANSPORTATION INFORMATION**

**DOT** NON REGULATED

## **XV. REGULATORY INFORMATION**

<b>Chemical Name</b>	<b>Regulation</b>	<b>CASRN</b>	<b>%</b>
Ammonia	SARA 313 Reportable:	7664-41-7	0.06
Formaldehyde	SARA 313 Reportable:	50-00-0	0.00
Ammonia	Extremely Haz. Substances:	7664-41-7	0.06
TPQ = 500 pounds; RQ = 100 pounds (does not meet toxicity criteria but because of high production volume and recognized toxicity is considered a chemical of concern)	SARA Threshold Planning Quantity:	7664-41-7	0.06
Formaldehyde (gas)	California Proposition 65 Cancer List:	50-00-0	0.00
calcium carbonate	New Jersey Right To Know:	471-34-1	35.56
Barium Sulfate	New Jersey Right To Know:	7727-43-7	23.95
Emulsion	New Jersey Right To Know:		
acrylic non volatiles	New Jersey Right To Know:	PROPRIETARY	9.26
propylene glycol	New Jersey Right To Know:	57-55-6	5.75

## **XVI. ADDITIONAL INFORMATION**

---

**Other Information:**

IMPORTANT: WHILE THE DESCRIPTIONS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU PERFORM AN ASSESSMENT TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED, DATA OR INFORMATION SET FORTH. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, OR DATA PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, THE DESCRIPTIONS, DATA AND INFORMATION FURNISHED HEREUNDER ARE GIVEN GRATIS. NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DATA AND INFORMATION GIVEN ARE ASSUMED. ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

MSDS glossary.